

# MINI-JARRAFF TECHNICAL SPECIFICATIONS



<b>Engine</b>	Air-cooled 46HP [34kW] 3 Cylinder T4i Deutz Engine
<b>Frame</b>	Steel Construction, Articulated Steering, Self-leveling, Adjustable Track Width
<b>Hydraulics</b>	Individual 2 Speed Hydraulic Wheel Drives With Mechanical Disconnect
<b>Hydraulic Tank</b>	20 Gal [76L] Capacity; Cenex Hydrostatic ISO 46 Oil
<b>Fuel Tank</b>	29 Gal [110L] Capacity; Diesel Fuel
<b>Boom</b>	55' (16.8m) Vertical Reach
<b>Construction</b>	Telescoping Belt Drive Non-conductive Fiberglass Boom
<b>Saw Head</b>	24" [610mm] Diameter Circular Blade With 180° Rotation Open Loop Proportionally Controlled Functions With Load Sensing
<b>Operation</b>	Frequency Jumping Remote Control System That Meets All Safety Regulations, Rechargeable Lithium Ion Batteries As Well As Hard Link Tether
<b>Tires</b>	15.50-15.00 HIPPO R4
<b>Machine Dimensions</b>	Tires: Min/Max Width - 48" [1.2m] / 126" [3.2m] Minimum Overall Length: 30' [9.2m]
<b>Safety</b>	Programmed Stability Parameters, Operator Trip/Fall Detection, Inactivity Timeout, Saw Brake, Dual 20lb Fire Extinguishers, Amber Warning Lights, Interactive Display, Recovery Straps Front And Rear.
<b>Diagnostics</b>	Remote Telematic Diagnostics, Monitoring And Error Logging With On Screen Troubleshooting Capability.
<b>GVW</b>	9,540 lbs [4,328 Kg] WET

Specifications subject to change.

